

## ST 200 SERİSİ TANDEM YUMUŞATMA SİSTEMLERİ TEKNİK ÖZELLİKLER

Model	Debi m <sup>3</sup> /saat			Kapasite (m <sup>3</sup> xFr)	Mineral Miktar (lt)	Tuz Tüketimi (kg)	Tank Boyut		Bağlantı
	Ort.	Max.	Ters Yıkama				DxH (cm)	D"xH"	
ST 20/P8-1"	0,7	1,5	0,5	120	2 x 20	3	20x89	8x35	1"
ST 30/P10-1"	1,0	2,0	0,7	180	2 x 30	5	25x89	10x35	1"
ST 50/P10-1"	1,0	2,0	0,7	300	2 x 50	8	25x137	10x54	1"
ST 75/P13-1"	1,7	3,4	1,3	450	2 x 75	12	33x165	13x54	1"
ST 100/P14-1"	1,9	3,8	1,4	600	2 x 100	16	35x165	14x65	1"
ST 125/P16-1"	2,5	4,0	1,9	750	2 x 125	20	40x165	16x65	1"
ST 125/P16-1"1/4	2,5	5,0	1,9	750	2 x 125	20	40x165	16x65	1"1/4
ST 125/P16-1"1/2	2,5	5,0	1,9	750	2 x 125	20	40x165	16x65	1"1/2
ST 150/P18-1"1/4	3,5	6,9	2,6	900	2 x 150	24	47x165	18x65	1"1/4
ST 150/P18-1"1/2	3,5	6,9	2,6	900	2 x 150	24	47x165	18x65	1"1/2
ST 200/P21-1/4	4,7	7,7	3,6	1200	2 x 200	32	53x151	21x60	1"1/4
ST 200/P21-1"1/2	4,7	8,0	3,6	1200	2 x 200	32	53x151	21x60	1"1/2
ST 200/P21-2"	4,7	9,5	3,6	1200	2 x 200	32	53x151	21x60	2"
ST 300/P24-1"1/2	5,8	10	4,4	1800	2 x 300	48	61x175	24x72	1"1/2
ST 300/P24-2"	5,8	11,7	4,4	1800	2 x 300	48	61x175	24x72	2"
ST 450/P30-2"	9,3	18	7,0	2700	2 x 450	72	77x181	30x72	2"
ST 600/P36-2"	13,6	19,5	10,2	3600	2 x 600	96	93x185	36x72	2"
ST 600/P36-3"	13,6	27,2	10,2	3600	2 x 600	96	93x185	36x72	3"
ST 800/P42-2"	18	23	13,5	4800	2 x 800	128	107x201	42x72	2"
ST 800/P42-3"	18	35	13,5	4800	2 x 800	128	107x201	42x72	3"
ST 1200/P48-2"	23	23	17,5	7200	2 x 1200	192	122x205	48x72	2"
ST 1200/P48-3"	23	45	17,5	7200	2 x 1200	192	122x205	48x72	3"