

## S 200 SERİSİ TEKLİ YUMUŞATMA SİSTEMLERİ TEKNİK ÖZELLİKLER

Model	Debi m <sup>3</sup> /saat			Kapasite (m <sup>3</sup> xFr)	Mineral Miktar (lt)	Tuz Tüketimi (kg)	Tank Boyut		Bağlantı
	Ort.	Max.	Ters Yıkama				DxH (cm)	D"xH"	
S 50/P10-1"	1,0	2,0	0,7	300	50	8	25x137	10x54	1"
S 75/P13-1"	1,7	3,4	1,3	450	75	12	33x165	13x54	1"
S 100/P14-1"	1,9	3,8	1,4	600	100	16	35x165	14x65	1"
S 125/P16-1"	2,5	5,0	1,9	750	125	20	40x165	16x65	1"1/4
S 150/P18-1"1/4	3,5	6,9	2,6	900	150	24	47x165	18x65	1"1/4
S 150/P18-1"1/2	3,5	6,9	2,6	900	150	24	47x165	18x65	1"1/2
S 200/P21-1/4	4,7	9,5	3,6	1200	200	32	53x151	21x60	1"1/4
S 200/P21-1"1/2	4,7	9,5	3,6	1200	200	32	53x151	21x60	1"1/2
S 300/P24-1"1/2	5,8	10	4,4	1800	300	48	61x175	24x72	1"1/2
S 300/P24-2"	5,8	11,7	4,4	1800	300	48	61x175	24x72	2"
S 450/P30-2"	9,3	18	7,0	2700	450	72	77x181	30x72	2"
S 600/P36-2"	13,6	19,5	10,2	3600	600	96	93x185	36x72	2"
S 600/P36-3"	13,6	27,2	10,2	3600	600	96	93x185	36x72	3"
S 800/P42-2"	18	23	13,5	4800	800	128	107x201	42x72	2"
S 800/P42-3"	18	35	13,5	4800	800	128	107x201	42x72	3"
S 1200/P48-2"	23	23	17,5	7200	1200	192	122x205	48x72	2"
S 1200/P48-3"	23	45	17,5	7200	1200	192	122x205	48x72	3"